





ISO 9001:2015 Certified Company

FIBERGLASS DUCT RODDER

- Continuous Pipe and Duct Rodding systems gives a compact and labour saving solution whether installing cables in ducts.
- The duct rod itself reliable and manufactured from the highest quality fiberglass radially reinforced construction available in a choice of diameters
- All rods are mounted on rugged and robust zinc plated steel frame.



Item Code	DUR 4510	DUR 0610	DUR 0810	DUR 9150	DUR 1110	DUR 1115	DUR 1120	DUR 1130
Duct Rod Size (mm x meter)	Ø4.5 x 100	Ø6 x 100	Ø8 x 100	Ø9 x 150	Ø11 x 100	Ø11 x 150	Ø11 x 200	Ø11 x 300
Curvature (mm)	70	90	130	130	170	170	170	170
Pipe Diameter (mm)	Ø40-Ø60	Ø50-Ø80	Ø63-Ø125	Ø63-Ø125	Ø63-Ø150	Ø63-Ø150	Ø63-Ø150	Ø63-Ø150
Breaking Strength (kg)	880	1600	3600	3600	5520	5520	5520	5520
Pulling Strength (kg)	140	180	270	270	400	400	400	400

As a manufacturer, we will endeavor to make the customer specification to suit your individual requirements.