

FIBERGLASS DUCT RODDER

- Specialized to guide underground telecommunication cables and power cable laying.
- Powder Coated metallic reel with embedded break.
- Two rod-out guides, giving ability to work in 2 directions, with curved edges avoiding damage of the PP surface.
- Operates in Horizontal and vertical position.
- Ergonomic design for better usage when: lift, carry and lay down the duct rodder.
- Steel brake for maximum durability with plastic grip for comfortable handling.



Item Code	DRE 4510	DRE 0610	DRE 9100	DRE 9150	DRE 1110	DRE 1115	DRE 1120	DRE 1130
Duct Rod Size (mm x meter)	Ø4.5 x 100	6 x 100	9 x 100	9 x 150	11 x 100	11 x 150	11 x 200	11 x 300
Curvature (mm)	90	110	170	170	220	220	220	220
Pipe Diameter (mm)	Ø40-Ø60	Ø50-Ø80	Ø63-Ø125	Ø63-Ø150	Ø63-Ø200	Ø63-Ø200	Ø63-Ø200	Ø63-Ø200
Breaking Strength (kg)	1100	2000	4500	4500	6900	6900	6900	6900
Pulling Strength (kg)	170	230	340	340	500	500	500	500

❖ As a manufacturer, we will endeavor to make the customer specification to suit your individual requirements.